



## **30X Zoom**

### **7" IR Variable Speed Dome GA-BA70B**

- \* Support multiple scans;
- \* Adaptive Pelco P/D protocol;
- \* Lightning proof and surge proof;
- \* 128 preset positions, support lens;
- \* Stepper motor less heat, runs steady, no shaking;
- \* Better magnetic shield and heat radiation;
- \* Proportional zoom and auto flip function;
- \* Auto running memory against power outage;
- \* According to the zoom adjust the strength of IR lights;
- \* 8pcs LED Array IR lights, night vision distance up to 150 meters;
- \* IR LEDs and Lens are always synchronized, no blind monitor position.

Model	7" LED-Array IR Variable Speed Dome Camera GA-BA70B
Power Supply	Output: DC12V±5%,5A; Input:AC100V~240V 50/60Hz
Power (Max.)	15W (IR OFF) 36W(IR ON) 46W(with heater)
Pan/Tilt Speed	1°~25°/sec
Pan Range	0°~360°Continuous
Tilt Range	0°~90°
Preset	128
Preset Accuracy	±0.3°
Cruise	4 groups.16 presets/group
Tour	speed adjustable (6° , 15° ,20° auto /sec)
Pattern	4 groups, 180secs/ group

IR Light	Default: 6 times, open middle-distance lights; 10 times, open far-distance lights.
Communication	RS485
Baud Rate	2400bps,4800bps,9600bps,19200bps
Protocol	Pelco-P/D auto detected
Address	1~255
Work Temperature	Indoor: 0°C~50°C Outdoor: -20°C~50°C(with heater)